

AQUAFIN PLUNGE SINGLE / FINSAUNA

FEATURES

- Hot or cold immersion with precise temperature control through touchpad or Wi-Fi app
- 2 powerful hydrotherapy jets and immersive LED lighting
- Anti-spillover design for water retention
- Solid, sturdy ABS bottom for easy placement
- Bottom floor drain and condensation pan for water/moisture control
- Outdoor ASTM safety-rated, tapered & lockable woven fiber cloth cover
- 6-layer closed-cell polyurethane and foil on shell, cabinet, bottom and plumbing for insulation and longevity
- Optional saltwater capability
- Optional ozone capability



SPECIFICATIONS

Model: AQUAFIN PLUNGE SOLO

Capacity: 1 Person

Shell Material: : Lucite Acrylic with Fiberglass

Insulation Type: 6-Layer closed-cell polyurethane and foil on shell, cabinet, bottom, and plumbing

Voltage: 120v

Lighting: LED Lighting

Flooring: ABS

Water Capacity: 120 gal.

Dimensions (approx.):

W: 85" x D: 42" x H: 30"

Heater and Control Options:

Digital touchpad control

DIMENSIONS (O.D.)

General Information	
Dimensions (L x W x H)	85" x 42" x 30"
Dry & filled weights	360 lbs dry / 1400 lbs with water
Water capacity	120 gallons
Seating capacity	1 person
Electrical requirements	120v. 15 amp plug-in
Features	Anti-spillover design, Solid ABS bottom, Free Wi-Fi App, floor bottom drain, condensation pan
Convenience Features	
Ozone ready?	Yes - Corona Discharge with mixing chamber included as standard equipment
Saltwater-ready?	Yes (optional)
Power indicator	Integrated into metal nameplate
Lighting	LED lighting
Filter size	50 sq. ft.
Filter media type	Reemay Polyester
Tub specifications	
Shell material	Lucite Acrylic with Fiberglass
Insulation type	6-layer closed-cell polyurethane and foil on shell, cabinet, bottom, and plumbing
Cover included?	Yes
Cover type	Outdoor ASTM safety-rated, tapered & lockable woven fiber cloth cover
Skirt material	Synthetic Poly
Mini Split specifications	
Control type	Digital touchpad control
Mini-Split placement	Under-skirt
Mini Split construction material	Titanium Coil
Lowest temperature attainable	37°F - 3°C
Circulation pump	Yes - thermo-sensitive controlled
Chilling mode	3-position (Silent mode 1 degree/hour, Intelligent/Smart mode 3 degrees/hour, Powerful mode 5 degrees/hour)
Safety	
Safety rating/certification	ETL safety listed
GFCI location	Built-in to power cord
Warranty	
Equipment parts warranty	1 year
Shell warranty	3 years

AQUAFIN PLUNGE DOUBLE / FINSAUNA

FEATURES

- Hot and cold immersion with precise temperature control through touchpad or Wi-Fi app
- 12 massage jets powered by True 1 Hp Hydrotherapy pump on hot side
- Immersive LED lighting
- Anti-spillover design for water retention
- Solid, sturdy ABS bottom for easy placement
- Bottom floor drain and condensation pan for water/moisture control
- Outdoor ASTM safety-rated, tapered & lockable woven fiber cloth cover
- 6-layer closed-cell polyurethane and foil on shell, cabinet, bottom and plumbing for insulation and longevity
- Optional saltwater capability
- Optional ozone capability



SPECIFICATIONS

Model: AQUAFIN PLUNGE DOUBLE

Capacity: 1 Person (Cold) / 2 Person (Hot)

Shell Material: : Lucite Acrylic with Fiberglass

Insulation Type: 6-Layer closed-cell polyurethane and foil on shell, cabinet, bottom, and plumbing

Voltage: 240v

Lighting: LED Lighting

Flooring: ABS

Water Capacity: 120 gallons (Cold)/
130 gallons (Hot)

Dimensions (approx.):

W: 85" x D: 85" x H: 30"

Heater and Control Options:

Digital touchpad control

DIMENSIONS (O.D.)

General Information	
Dimensions (L x W x H)	85" x 85" x 30"
Dry & filled weights	750 lbs dry / 2875 lbs with water
Water capacity	120 gallons (Cold) / 130 gallons (Hot)
Seating capacity	1 person (Cold) / 2 persons (Hot)
Electrical requirements	50-amp 240v hard-wired connection
Features	Anti-spillover design, Solid ABS bottom, Free Wi-Fi App, bottom floor drain, condensation pan
Convenience Features	
Ozone ready?	2 Corona Discharge units with mixing chambers included as standard equipment
Saltwater-ready?	Yes (optional)
Power indicator	Integrated into metal nameplate
Lighting	LED lighting
Filter size / Media type	2x 25 sq. ft. Reemay Polyester in skimmer compartment
Hydrotherapy Jets / Hp	12 massage jets powered by True 1 Hp Hydrotherapy pump on hot side
Tub specifications	
Shell material	Lucite Acrylic with Fiberglass
Insulation type	6-layer closed-cell polyurethane and foil on shell, cabinet, bottom, and plumbing
Cover included?	Yes
Cover type	Outdoor ASTM safety-rated, tapered & lockable woven fiber cloth cover
Skirt material	Synthetic Poly
Mini Split specifications	
Control type	Digital touchpad control
Mini-Split placement	Under-skirt
Mini Split construction material	Titanium Coil
Temperature range	37°F - 3°C (Cold) / 104° F - 40° C (Hot)
Circulation pump	Yes - thermo-sensitive controlled
Chilling mode	3-position (Silent mode 1 degree/hour, Intelligent/Smart mode 3 degrees/hour, Powerful mode 5 degrees/hour)
Safety	
Safety rating/certification	ETL safety listed
GFCI location	Built-in to power cords on 120v plug-ins
Warranty	
Equipment parts warranty	1 year
Shell warranty	3 years